BMW MOTORRAD

R 1250 GS

Engine		
Туре	Air/liquid-cooled four stroke flat twin engine, double overhead camshaft, one balance shaft and	
	Variable engine timing system BMW Shift Cam	h S
Bore / stroke	102,5 mm x 76 mm	
Capacity Dated autout	1.254 cc	-10-50
Rated output Max. Torque	100 kW (136 PS) at 7.750 U/min	
Compression ratio	143 Nm at 6.250 U/min	
Mixture control	12.5 : 1 Electronic inteka manifold injection	
Emission control	Electronic intake manifold injection Regulated three-way catalytic converter, compliant with EU5 emission standard	Style Triple Black
Performance / fuel consumption	Quere 200 Line/h	\$ 248,800/Month HK\$4,809
Maximum speed	Over 200 km/h 4,75 l	
Fuel consumption per 100 km based on WMTC CO2	4,751 110 g/km	
emission based on WMTC	Unleaded super, octane number 95 (RON), adaptive fuel quality regulation (91 to 98 RON)	
Fuel type		the star
Electrical system Alternator	Three-phase alternator 510 W (nominal power)	
Battery	12 V / 11,8 Ah, Maintenance-free	
Power transmission Clutch	Wet clutch with an anti-hopping function, hydraulic activation	
Gearbox	Constant mesh 6-speed gearbox with helical gear teeth	Light white non-metallic
Drive	Constant mesh 6-speed gearbox with nelical gear teeth Shaft drive	\$248,800/ Month HK\$4,809
Chassis / brakes Frame	Two-section frame, front- and bolted on rear frame, load-bearing engine	
Front wheel location / suspension		
	Telelever; stanchion diameter 37 mm, central spring strut	
Rear wheel location / suspension	Cast aluminum single-sided swing arm with BMW Motorrad Paralever; WAD strut (Travel-related Damping), spring pre-load hydraulically adjustable (continuously variable) at hand wheel, rebound	
Suspension travel, front / rear	Damping adjustable at hand wheel	
Wheelbase (normal load)	190 mm / 200 mm	
Castor (normal load)	1.514 mm	
Steering head angle (normal load)	100.6 mm	
Wheels	64.3°	
	Cast aluminum wheels	Style Rallye
Rim, front	3,00 x 19"	\$258,800/Month HK\$5,002
Rim, rear	4,50 x 17"	
Tyre, front	120/70 R 19	
Tyre, rear	170/60 R 17	
Brake, front	Dual disc brake, floating brake discs, diameter 305 mm, 4-piston radial calipers	
Brake, rear	Single disc brake, diameter 276 mm, double-piston floating caliper	
ABS	BMW Motorrad Integral ABS Pro (part-integral, slant-layer-optimized)	And
		3366
Dimensions / weights Seat height	850 / 870 mm (lowered suspension* 800 / 820 mm) *OE	
Inner leg curve	1870/1910 mm (lower seat height* 1750 / 1790 mm) *OE	
Usable tank volume	201	
	approx. 4 l	Edition 40 Years GS
Reserve	2.207 mm	\$265,800/Month HK\$5,138
Length (over mud guard)	1.430 mm	ΨΖΟΞ,ΟΟΟΙ Month HK\$5,138
Height (over windshield)	952,5 mm	
Wide (over mirror)	294 249 kg	
Unladen weight, road ready, fully fuelled	465 kg	
Permitted total weight Payload (with standard equipment)	216 kg	
Equipment (in parts)		Optional equipment
	-TFT rider information display with connectivity,	FRT included
Standard equipment	-HEADLIGHT PRO & ADAPTIVE HEADLIGHT, -ASC (Automatic Stability Control)	- Engine Bar \$ 5,024
and the first state of the stat	-KEYLESS RIDE	- HP sports silencer \$14,580
	-HAND PROTECTION -CRUISE CONTROL	- HP Battery \$ 4,050
	-HSC (Hill Start Control),	- Billet Pack \$25,000
	-Chrome-plated exhaust pipe -HEATED GRIPS	- Anti theft alarm \$3,320

-UNDE CONTROL +HSC (Hill Start Control), -Chrome-plated exhaust pipe -HEATED GRIPS -Cruising Light -TYRE PRESSURE CONTROL -MSR (Dynamic engine brake control) -RIDING MODES PRO -PREPARATION FOR GPS DEVICE -DYNAMIC ESA -GEAR SHIFT ASSISTANT PRO