



KAWASAKI - D-Tracker 125



SPECIFICATIONS

Engine Type	Air-cooled, 4-stroke Single
Displacement	125 cm ³
Bore x stroke	54.0 x 54.4 mm
Compression ratio	9.5:1
Valve/Induction system	SOHC, 2 valves
Maximum power	7.6 kW {10.3 PS} / 8,000 rpm
Maximum torque	10.0 N.m {1.0 kgf.m} / 6,400 rpm
Fuel system	Fuel injection: ø20 mm x 1 (Keihin)
Ignition	Digital DC-CDI
Starting	Electric
Transmission	5-speed, return
Final Drive	Chain
Clutch	Wet multi-disc, manual
Frame type	Perimeter, steel
Suspension, front	35 mm inverted fork
Suspension, rear	New Uni-Trak
Tyre, front	100/80-14M/C 48P
Tyre, rear	120/80-14M/C 58P
Brakes, front	Single 240 mm petal disc Twin-piston
Brakes, rear	Single 190 mm petal disc Single-piston
Dimensions (L x W x H)	1,900 mm x 770mm x 1,060mm
Wheelbase	1,255 mm
Seat height	805 mm
Fuel capacity	7.0 litres
Dry weight	114kg



Titanic Moto Centre Limited
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.

香港北角規殼街9-23號秀明中心地下A舖

Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228