



KAWASAKI - 1400GTR

SPECIFICATIONS



Engine Type	Liquid-cooled, 4-stroke Inline-Four
Displacement	1,352 cm ³
Bore x stroke	84.0 x 61.0 mm
Compression ratio	10.7 : 1
Valve/Induction system	DOHC, 16 valves
Maximum power	155 PS / 8,800 rpm
Maximum torque	13.9 kgf-m / 6,200 rpm
Fuel system	Fuel Injection: 40 mm x 4 oval sub-throttles
Ignition	Digital
Starting	Electric
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Monocoque, pressed-aluminium
Suspension, front	43 mm inverted fork
Suspension, rear	Bottom-Link Uni-Trak with gas charged shock
Tyre, front	120/70ZR17 M/C (58W)
Tyre, rear	190/50ZR17 M/C (73W)
Brakes, front	Dual semi-floating 310 mm petal discs Caliper: Dual radial-mount, opposed 4-piston
Brakes, rear	Single 270 mm petal disc Caliper: twin-piston
Dimensions (L x W x H)	2,270 mm x 1,000 mm x 1,290 mm
Wheelbase	1,520 mm
Seat height	815 mm
Fuel capacity	22 litres
Dry weight	279 kg



Titanic Moto Centre Limited
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.
香港北角蜆殼街9-23號秀明中心地下A舖
Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228