

KAWASAKI - KLX250



SPECIFICATIONS

Engine Type	Liquid-cooled, 4-stroke Single
Displacement	249 cm ³
Bore x stroke	72.0 x 61.2 mm
Compression ratio	11.0 : 1
Valve/Induction system	DOHC, 4 valves
Maximum power	22 PS / 7,500 rpm
Maximum torque	2.1 kgf-m / 7,000 rpm
Fuel system	Fuel Injection
Ignition	Digital
Starting	Electric
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Perimeter, high-tensile steel
Suspension, front	43 mm inverted fork
Suspension, rear	Uni-Trak with gas charged shock
Tyre, front	3.00-21 51P
Tyre, rear	4.60-18 63P
Brakes, front	Single 250 mm petal disc Caliper: twin-piston
Brakes, rear	Single 240 mm petal disc Caliper: twin-piston
Dimensions (L x W x H)	2,200 mm x 820 mm x 1,205 mm
Wheelbase	1,430 mm
Seat height	890 mm
Fuel capacity	7.7 litres
Dry weight	127 kg



Titanic Moto Centre Limited
 G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.
 香港北角規殼街9-23號秀明中心地下A舖
 Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228