



KAWASAKI - KLX450R



SPECIFICATIONS

Engine Type	Liquid-cooled, 4-stroke Single
Displacement	449 cm ³
Bore x stroke	96.0 x 62.1 mm
Compression ratio	12.0 : 1
Valve/Induction system	DOHC, 4 valves
Maximum power	56.4 PS / 8,500 rpm
Maximum torque	5.18 kgf-m / 7,000 rpm
Fuel system	Carburetor: Keihin FCR40
Ignition	Digital
Starting	Electric
Transmission	5-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Perimeter, aluminium
Suspension, front	48 mm inverted fork
Suspension, rear	Uni-Trak with gas charged shock
Tyre, front	80/100-21 M/C 51P
Tyre, rear	120/90-18 M/C 65P
Brakes, front	Single semi-floating 250 mm petal disc Caliper: twin-piston
Brakes, rear	Single 240 mm petal disc Caliper: single-piston
Dimensions (L x W x H)	2,175 mm x 820 mm x 1,250 mm
Wheelbase	1,480 mm
Seat height	935 mm
Fuel capacity	8 litres
Dry weight	115 kg



Established
1971

Titanic Moto Centre Limited
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.
香港北角蜆殼街9-23號秀明中心地下A舖
Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228