



KAWASAKI - KX85 / KX85 II



SPECIFICATIONS

Engine Type	Liquid-cooled, 2-stroke Single with KIPS
Displacement	84 cm ³
Bore x stroke	52.0 x 45.8 mm
Compression ratio	Low Speed: 9.6:1 / High Speed:8.8:1
Valve/Induction system	2-Petal Carbon-fibre piston reed valve
Fuel system	Carburettor: Keihin PWK28
Ignition	Digital CDI
Starting	Primary Kick
Transmission	6-speed, return
Final Drive	Chain
Clutch	Wet multi-disc, manual
Frame Type	Perimeter, high tensile steel
Tyre: Front	70/100-17 40M / 70/100-19 42M (KX85II)
Tyre: Rear	90/100-14 49M / 90/100-16 52M (KX85II)
Trail	89mm (103mm for KX85 II)
Steering angle (left/right)	45° / 45°
Suspension: Front	36mm upside-down telescopic fork / 18 way
Suspension: Rear	Bottom-link Uni-Trak / 4 way
Brakes, front	Single 220mm disc Caliper: Dual-piston
Brakes, rear	Single 184mm disc Caliper: single-piston
Dimensions (L x W x H)	1,820 mm x 735 mm x 1,055 mm 1,910mm x 735mm x 1,105mm for KX85II
Wheelbase	1,255mm / 1,290mm for KX85II
Seat height	840 mm / 870mm for KX85II
Fuel capacity	5.5 litres
Dry Weight	65 kg / 68kg for KX85II



Titanic Moto Centre Limited
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.
香港北角蜆殼街9-23號秀明中心地下A舖
Tel :(+852) 2512 2228 Email :support@titanicmoto.com Fax : (+852) 2566 9228