



## KAWASAKI - VN900 CUSTOM



### SPECIFICATIONS

Engine Type	Liquid-cooled, 4-stroke V-Twin
Displacement	903 cm <sup>3</sup>
Bore x stroke	88.0 x 74.2 mm
Compression ratio	9.5 : 1
Valve/Induction system	SOHC, 8 valves
Maximum power	54 PS / 6,000 rpm
Maximum torque	8.4 kgf-m / 3,500 rpm
Fuel system	Fuel Injection: 34 mm x 2 Dual throttle valves
Ignition	Digital
Starting	Electric
Transmission	5-speed, return
Final Drive	Belt
Clutch	Wet multi-disc, manual
Frame type	Double-cradle, steel
Suspension, front	41 mm telescopic fork
Suspension, rear	Uni-Trak
Tyre, front	89/90-21 M/C (48H)
Tyre, rear	180/70-15 M/C (76H)
Brakes, front	Single 300 mm disc Caliper: Twin-piston
Brakes, rear	Single 270 mm disc Caliper: Twin-piston
Dimensions (L x W x H)	2,405 mm x 895 mm x 1,120 mm
Wheelbase	1,645 mm
Seat height	685 mm
Fuel capacity	20 litres
Dry weight	250 kg



**Titanic Moto Centre Limited**  
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.  
香港北角蜆殼街9-23號秀明中心地下A舖  
Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228