



KAWASAKI - NINJA ZX-10R



SPECIFICATIONS

Engine Type	Liquid-cooled, 4-stroke In-line Four
Displacement	998cm ³
Bore x stroke	76.0 x 55.0 mm
Compression ratio	13.0 : 1
Valve/Induction system	DOHC, 16 valves
Maximum power	200.1PS / 209.9 (with Ram-Air) / 13,000rpm
Maximum torque	112N.m (11.2 kgf.m) / 7,800 rpm
Fuel system	Fuel Injection: Ø47 mm x 4 (Keihin) with oval sub-throttles, dual injection
Ignition	Digital
Starting	Electric
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Twin spar, cast aluminium
Suspension, front	43 mm inverted fork
Suspension, rear	Horizontal Back-link, gas charged
Tyre, front	120/70 ZR17
Tyre, rear	190/50 ZR17
Brakes, front	Dual semi-floating 310 mm petal discs, 10 button
Caliper	Dual radial-mount, opposed 4 (aluminium) piston
Brakes, rear	Single 220 mm petal disc
Caliper	Single-bore pin-slide, aluminium piston
Dimensions (L x W x H)	2,075 mm x 715 mm x 1,115 mm
Wheelbase	1,425 mm
Seat height	813 mm
Fuel capacity	17 litres
Curb Mass	218 kg / 201kg



Titanic Moto Centre Limited
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong.
香港北角蜆殼街9-23號秀明中心地下A舖
Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228