

# Kawasaki

**KAWASAKI – KLR650** (2012) ~ Let the good times roll ~



## SPECIFICATIONS



Engine Type	Liquid-cooled, 4-stroke, Single
Displacement	651 cm <sup>3</sup>
Bore x stroke	100.0 x 83.0 mm
Compression ratio	9.8 : 1
Valve/Induction system	DOHC, 4 valves
Fuel system	Carburettor: CVK40
Ignition	Full Transistor
Starting	Electric
Transmission	5-speed, return
Final Drive	Chain
Clutch	Wet multi-disc, manual
Frame type	Semi-double cradle, high-tensile steel
Suspension, front	41 mm telescopic fork
Suspension, rear	Uni-Trak
Rebound damping	Stepless
Spring preload	5-way
Tyre, front	90/90-21 M/C 54S
Tyre, rear	130/80-17 M/C 65S
Brakes, front	Single 280 mm petal disc Caliper: twin-piston
Brakes, rear	Single 240 mm petal disc Caliper: twin-piston
Dimensions (L x W x H)	2,295 mm x 960 mm x 1,350 mm
Wheelbase	1,480 mm
Seat height	890 mm
Fuel capacity	22.1 litres
Dry weight	175 kg



**Titanic Moto Centre Limited 泰力摩托車中心**  
G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong  
香港北角蜆殼街9-23號秀明中心地下A舖  
Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9555  
[www.titanicmoto.com](http://www.titanicmoto.com)



æel