



KAWASAKI – Ninja 250R (2012)

~ Let the good times roll ~



SPECIFICATIONS

Engine Type	Liquid-cooled, 4-stroke Parallel Twin
Displacement	249 cm ³
Bore x stroke	62.0 x 41.2 mm
Compression ratio	11.6 : 1
Valve/Induction system	DOHC, 8 valves
Maximum power	33 PS / 11,000 rpm
Maximum torque	22 N·m {2.24 kg·m} / 9,500 rpm
Fuel system	Fuel Injection: 28 mm x 2, Dual throttle valves Carburettor: Keihin CVK30 x 2 (EX250J)
Ignition	Digital
Starting	Electric
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Tube diamond, steel
Suspension, front	37 mm telescopic fork
Suspension, rear	Bottom-Link Uni-Trak with gas-charged shock and 5-way adjustable preload
Tyre, front	110/70-17 M/C (54S)
Tyre, rear	130/70-17 M/C (62S)
Brakes, front	Single 290 mm petal disc Caliper: Single balanced dual piston
Brakes, rear	Single 220 mm petal disc Caliper: Dual-piston
Dimensions (L x W x H)	2,085 mm x 715 mm x 1,115 mm
Wheelbase	1,400 mm
Seat height	775 mm
Fuel capacity	17 litres
Dry weight	154kg



泰力摩托車中心

Titanic Moto Centre Limited

G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, HK

香港北角蜆殼街9-23號秀明中心地下A舖

www.titanicmoto.com

Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228