

Kawasaki

KAWASAKI – W800 (2012)

~ Let the good times roll ~



SPECIFICATIONS



Engine Type	Air-cooled, 4-stroke Vertical Twin
Displacement	773 cm ³
Bore x stroke	77.0 x 83.0 mm
Compression ratio	8.4:1
Valve/Induction system	SOHC, 8 valves
Maximum power	35.0 kW { 48 PS } / 6,500 rpm (EUR)
Maximum torque	60.0 N.m {6.1 kgf.m} / 2,500 rpm (EUR)
Fuel system	Fuel injection: ø34 mm x 2 with sub-throttles
Ignition	Digital
Starting	Electric
Transmission	5-speed, return
Final Drive	Chain
Clutch	Wet multi-disc, manual
Frame type	Double-cradle, high-tensile steel
Suspension, front	39 mm telescopic fork
Suspension, rear	Twin shocks
Spring preload	5-way
Tyre, front	100/90-19M/C 57H
Tyre, rear	130/80-18M/C 66H
Brakes, front	Single 300 mm disc Caliper: Twin-piston
Brakes, rear	Drum, 160 mm
Dimensions	(L x W x H) 2,190mm x 790mm x 1,075 mm
Wheelbase	1,465 mm
Seat height	790 mm
Fuel capacity	14 litres
Curb Mass	217 kg



泰力摩托車中心

Titanic Moto Centre Limited

G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, Hong Kong

香港北角蜆殼街9-23號秀明中心地下A舖 www.titanicmoto.com

Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228