



KAWASAKI – ZX 10R (2012)

~ Let the good times roll ~



SPECIFICATIONS



Engine Type Liquid-cooled, 4-stroke In-line Four
 Displacement 998cm³
 Bore x stroke 76.0 x 55.0 mm
 Compression ratio 12.9:1
 Valve/Induction system DOHC, 16 valves
 Maximum power **200PS** (with Ram-Air) / 12,500rpm
 Maximum torque 113N.m (11.5 kgf.m) / 8,700 rpm
 Fuel system Fuel Injection: Ø47 mm x 4 (Keihin) with oval sub-throttles, dual injection

Ignition Digital
 Starting Electric
 Transmission 6-speed, return
 Final Drive Sealed chain
 Clutch Wet multi-disc, manual
 Frame type Twin spar, cast aluminium
 Suspension, front 43 mm inverted fork
 Suspension, rear Horizontal Back-link, gas charged
 Tyre, front 120/70 ZR17
 Tyre, rear 190/50 ZR17
 Brakes, front Dual semi-floating 310 mm petal discs, 10 button
 Caliper Dual radial-mount, opposed 4 (aluminium) piston
 Brakes, rear Single 220 mm petal disc
 Caliper Single-bore pin-slide, aluminium piston
 Dimensions (L x W x H) 2110 x 710 x 1135mm
 Wheelbase 1415mm
 Seat height 830mm
 Fuel capacity 17 litres
 Curb Mass 208Kg



泰力摩托車中心

Titanic Moto Centre Limited

G/F, Shop A, Seabright Plaza, 9-23 Shell Street, North Point, HK

香港北角蜆殼街 9 - 23 號秀明中心地下A舖

www.titanicmoto.com

Tel : (+852) 2512 2228 Email : support@titanicmoto.com Fax : (+852) 2566 9228